

PERFECTION SHINGLES

LIFETIME LIMITED WARRANTY



CARE AND MAINTENANCE

While Kaycan vinyl siding remains virtually maintenance free, it will become dirty as any other product which is exposed to atmospheric conditions. Normally, your Kaycan vinyl siding can be cleaned satisfactorily through the use of an ordinary garden hose. If stubborn stains cannot be removed with water, the following procedure should be used:

1. Equip the garden hose with a soft bristled, long handle car brush.
2. Where soil is of a stubborn nature, the following cleaning solution works well:
 - 1/3 cup household detergent
 - 2/3 cup trisodium phosphate
 - 1 gallon of water

In certain geographic areas where mildew may be a problem, substitute one quart of 5% sodium hypochloride (household bleach) for one quart water in the above formula.

Where the house is extremely dirty, it is recommended that you start washing from the bottom and go to the top, rinsing frequently. Cleaning solutions should be permitted to stand on the surface of the siding for several minutes before rinsing.

THE VINYL SIDING INSTITUTE'S IMPORTANT FIRE SAFETY INFORMATION STATEMENT IS AS FOLLOWS:

Exterior vinyl building materials require little maintenance for many years. Nevertheless, common sense dictates that builders and suppliers of vinyl products store, handle and install vinyl materials in a manner that avoids damage to the product and/or structure. Owners and Installers should take a few simple steps to protect vinyl building materials from fire.

TO HOME AND BUILDING OWNERS:

Rigid vinyl siding is made from organic materials and will melt or burn when exposed to a significant source of flame or heat. Building owners, occupants and outside maintenance personnel should always take normal precautions to keep sources of fire, such as barbecues, and combustible materials, such as dry leaves, mulch and trash away from vinyl siding.

TO THE BUILDING TRADES, SPECIFIERS, PROFESSIONALS AND TO DO-IT-YOURSELF INSTALLERS:

When rigid vinyl siding is exposed to significant heat or flame, the vinyl will soften, sag, melt or burn, and may thereby expose material underneath. Care must be exercised prior to installation when selecting underlayment materials because many underlayment materials are made from organic materials. All building materials should be installed in accordance with local, state and Federal building codes and fire regulations.

©2018 Kaycan. All rights reserved.
www.kaycan.com

PSWR-CAN-18

KAYCAN

KAYCAN

Place this card in an envelope and mail to:

Kaycan
3075 Trans Canada Highway
Pointe-Claire, QC H9R 1B4
Canada

Application for Transfer PERFECTION SHINGLES LIFETIME LIMITED WARRANTY

Application is hereby made for the transfer of the Kaycan warranty to:

(PRINT NAME)

The new owner of the premises upon which the original Kaycan vinyl siding installation was made. The undersigned certify the following: (PLEASE PRINT CLEARLY)

(NAME OF FORMER OWNER)

(LOCATION OF INSTALLATION ADDRESS)

(CITY) (STATE/PROVINCE) (ZIP/POSTAL CODE)

(DATE OF INSTALLATION) (DATE OF TRANSFER)

(SIGNATURE OF FORMER OWNER) (DATE)

I expressly assent to the terms of the Kaycan warranty.

(SIGNATURE OF NEW OWNER) (DATE)

